



General

PowerPro generating sets are skillfully designed monobloc units linking the technical capabilities of appropriately sized, world-renowned Volvo diesel engines with high performance, premium quality alternators. They provide a comprehensive range of machines offering long-life, efficiency and reliability. These units are recommended as prime power or stand-by sources for industrial, commercial and residential applications, suited to most ambient conditions likely to be encountered around the globe. All **PowerPro** generating sets benefit from the major component suppliers' international warranties and these are complemented by our full after-sales support and spares package.

Engine

- Turbo-charged, watercooled, multi-cylinder direct-injection.
- Mechanical fixed speed, electronic or electronic engine management governing (as confirmed on technical data sheet).
- Replaceable elements for fuel, oil and air filters (where appropriate).
- Requiring only lubricating oil, coolant, inhibitor, battery acid and fuel for immediate start up.
- Key start/stop operation, with heavy-duty dry-charged lead acid battery pack with connecting leads and charging system.
- Heavy-duty tropicalised radiator with fan and stone-guards.
- All sets include a daily-service fuel tank integral with the baseframe, complete with fill, vent and drain points, fuel feed and return lines and a contents gauge.
- All sets can also be supplied with free-standing tanks as an optional extra.

Alternator and Control Panel

- Alternator of single bearing design close-coupled to the engine to provide accurate alignment.
- Brushless, self exciting, self regulating and solid state AVR controlled.
- Regulation under full load is maintained to +/- 1.5% depending upon AVR type.
- Enclosed in fabricated steel shell with drip-proof air ducts.
- Tropically insulated windings to class 'H', built in accordance with BS 5000, VDE 0530, IEC 34, UTE 5100 and NEMA MG1-22 regulations.
- Vibration-isolated alternator-mounted sheet-steel control panel containing the following instrumentation:
 - Start/stop key switch with shutdown and status indicators.
 - AC ammeters, voltmeter and selector switch.
 - Dual-scale Frequency/RPM meter and Hours-run counter
 - Gauges for Oil pressure, Engine temperature and battery voltmeter.
 - Fuses, terminations, relays and transformers as appropriate.
 - Output rated moulded-case three pole circuit breaker.

Finish and Quality Control

An outstanding spray-painted finish for Volvo-engined gensets is achieved by using rust-inhibited high-gloss enamel paint, to a heavy-duty industrial specification, with the base-frame similarly treated in black.

Alternatively, clients may specify their own colour-scheme preferences.

Each set is custom-built, subject to comprehensive and rigorous inspection procedures prior to despatch and tested under full resistive load, with test certificates supplied on request.

Instruction manuals for both engine and alternator, together with wiring diagrams, heavy-duty compressed rubber anti-vibration mounts and a high-efficiency exhaust silencer system with flexible section are provided for each machine.

Optional Extras

- Automatic mains-failure control systems
- Multi-set or mains synchronisation and load sharing controls
- Acoustic and weather-protecting enclosures
- ISO containerised sets
- Mobile trailer units
- Consumable and overhaul spares package

POWERSOURCE PROJECTS LIMITED

Powersource Projects Limited PowerPro House Capital Park Industrial Estate
Combe Lane Wormley Surrey GU8 5TJ UK



Telephone (from UK): 0845 389 9333
Telephone (from outside UK): +44 1428 684980
Email: sales@power-source-pro.co.uk

Fax Sales: +44 (0)1428 687979
Fax Spares: +44 (0)1428 687799
Web: www.power-source-pro.co.uk

VOLVO *PowerPro* GENERATING SETS - 50HZ

Technical Data

Dimensions and Weights

Model	Engine	kVA - Prime	kVA - Standby	Aspiration	Cylinders	Arrangement	Governing	Fuel Consumption	L	W	H	Kg	CBM
PPV 84	TAD530GE	84	87	Turbo	4	In-line	Mechanical	19.1	210	75	165	1050	2.99
PPV 100	TAD531GE	100	106	Turbo	4	In-line	Mechanical	21.5	220	75	165	1200	2.99
PPV 125	TAD532GE	125	131	Turbo	6	In-line	Mechanical	28.4	235	75	175	1525	3.55
PPV 150	TAD731GE	150	156	Turbo	6	In-line	Mechanical	30.9	240	90	175	1600	4.53
PPV 180	TAD732GE	180	182	Turbo	6	In-line	Elec. Eng. Man.	40.3	260	100	195	1880	5.61
PPV 200	TAD733GE	200	212	Turbo	6	In-line	Elec. Eng. Man.	45.3	260	100	195	1975	5.72
PPV 250	TAD734GE	250	260	Turbo	6	In-line	Electronic	52.2	280	110	195	2250	7.15
PPV 275	TAD940GE	275	290	Turbo	6	In-line	Elec. Eng. Man.	57.5	300	110	200	2435	7.59
PPV 300	TAD941GE	300	320	Turbo	6	In-line	Elec. Eng. Man.	62.0	300	110	200	2435	7.59
PPV 325	TAD941GE	325	345	Turbo	6	In-line	Elec. Eng. Man.	66.9	300	110	200	2510	7.59
PPV 350	TAD1240GE	350	375	Turbo	6	In-line	Elec. Eng. Man.	66.3	300	115	205	2865	8.13
PPV 370	TAD1241GE	370	390	Turbo	6	In-line	Elec. Eng. Man.	76.2	300	115	205	3000	8.54
PPV 400	TAD1242GE	400	425	Turbo	6	In-line	Elec. Eng. Man.	83.0	315	115	205	3300	8.54
PPV 450	TAD1640GE	450	470	Turbo	6	In-line	Elec. Eng. Man.	91.0	315	130	215	3700	10.61
PPV 500	TAD1641GE	500	515	Turbo	6	In-line	Elec. Eng. Man.	101.0	350	130	215	3800	10.61
PPV 570	TAD1642GE	570	620	Turbo	6	In-line	Elec. Eng. Man.	116.0	370	130	215	3850	10.61
PPV 630	TWD1643GE	630	680	Turbo	6	In-line	Elec. Eng. Man.	126.0	345	145	220	4170	12.66

Notes:-

- All figures based on power factor of 0.8, engine manufacturers data at NTP and use of Newage alternators with output voltage of 400V
 - All dimensions and weights are approximate in cm's and kg's and CBM figures reflect an approximate packed volume.
 - Fuel consumption is based upon litres/hr @ 100% load assuming fuel meets standards laid down in ASTM-D2
 - Addition of options may change performance and dimension details shown above
 - Prime rating allows continuous operation with a 10% overload for any one hour in twelve.
- Standby is a continuous rating with no overload capacity and an annual limitation as to usage at full load.
- All data is given in good faith but is subject to change based upon our technical improvements or those notified by the major component suppliers

DISTRIBUTED BY